


CONTRACT AWARD	
CK09MERCER2019-12 ONE (1) FORD F550 SERVICE BODY TIRE TRUCK WITH CRANE AND INVERTER OR EQUIVALENT, FOR THE MERCER COUNTY HIGHWAY DIVISION AND THE MERCER COUNTY COOPERATIVE CONTRACT PURCHASING SYSTEM	
BID OPENING DATE : MAY 14, 2019	
CONTRACT TERM: JUNE 24, 2019 THROUGH JUNE 25, 2020	RES. NO. 2019-321
NAME OF RESPONDENT	WINNER FORD
ADDRESS	250 BERLIN ROAD
CITY, STATE, ZIP	CHERRY HILL, NJ 08034
CONTACT	LINDA HOFFMAN
TELEPHONE	856 214 0759
FAX	856 488 1915
E-MAIL	LHOFFMAN@WINNERFORD.COM
UNIT COST FOR ONE (1) 2019 FORD F550 12' BOX TRUCK WITH LIFT GATE OR EQUIVALENT	\$ 97,251.00
MANUFACTURER	FORD
MODEL	F550 XL CHASSIS
YEAR	2020
DELIVERY DATE	90 DAYS AFTER RECEIPT OF ORDER
EXCEPTIONS	SEE EXCEPTIONS PAGE
FATAL FLAW	NO

Approved as to Form and Legality

Date



 County Counsel

June 27, 2019

AWARD OF BID RECEIVED MAY 24, 2019 TO WINNER FORD FOR ONE (1) 2019 OR NEWER FORD F550 SERVICE BODY TIRE TRUCK WITH CRANE AND INVERTER FOR THE MERCER COUNTY HIGHWAY DIVISION AND THE MERCER COUNTY COOPERATIVE CONTRACT PURCHASING SYSTEM PERIOD: JUNE 24, 2019 THROUGH JUNE 25, 2020. TOTAL AMOUNT NOT TO EXCEED \$97,251.00 (CK09MERCER2019-12)

WHEREAS, the Mercer County Purchasing Department has advertised for bids for one (1) 2019 Ford F550 Service Body Tire Truck with crane and inverter for use by the Mercer County Highway Division and the Mercer County Cooperative Contract Purchasing System for a period of one (1) year, authorized by Resolution No. 2018-89, adopted February 8, 2018; and,

WHEREAS, one (1) sealed bid was received on May 24, 2019 in connection with the aforementioned procurement; and,

WHEREAS, the bidder hereinafter designated is the lowest qualified bidder; and,

.....
 Clerk to the Board

RECORD OF VOTE													
FREEHOLDER	Aye	Nay	N.V.	Abs.	Res.	Sec.	FREEHOLDER	Aye	Nay	N.V.	Abs.	Res.	Sec.
Cannon	X				✓		Melker	X					
Colavita	X					✓	Walter	X					
Frisby	X						Cimino				X		
Koontz	X												


X—Indicates Vote Abs.—Absent N.V.—Not Voting
 Res.—Resolution Moved Sec.—Resolution Seconded

WHEREAS, the bid received from Winner Ford, 250 Berlin Road, Cherry Hill, NJ 08034 meets the specifications and shall be awarded for one (1) 2019 Ford F550 Service Body Tire Truck with crane and inverter for use by the Mercer County Highway Division for the period of June 24, 2019 through June 25, 2020, an amount not to exceed \$97,251.00; and,

WHEREAS, the Chief Financial Officer of Mercer County has certified in writing the availability of funds for the purposes set forth in this Resolution; said certification is on file with the Clerk to the Board, now, therefore,

BE IT RESOLVED, that the County Executive and Clerk to the Board be and are hereby authorized to execute said contracts when presented in a form approved by County Counsel; and,

BE IT FURTHER RESOLVED, that the Clerk to the Board shall forward a copy of this Resolution to the Mercer County Department of Transportation and Infrastructure, Highway Division and the Mercer County Purchasing Department for further distribution.



.....
Clerk to the Board

SPECIFICATIONS ONE (1) FORD F550 SERVICE BODY TIRE TRUCK WITH CRANE AND INVERTER OR EQUIVALENT, FOR THE MERCER COUNTY HIGHWAY DIVISION AND THE MERCER COUNTY COOPERATIVE CONTRACT PURCHASING SYSTEM FOR USE BY MOTOR POOL

CONTACT PERSON: MOTOR POOL -JODI HAWRYLUK (609) 530-7525

INTENT

The County of Mercer requests bids for One (1) Ford F550 Service Body Tire Truck with Crane and Inverter or Equivalent. The County requests the bid price to be held for one year. Bids shall be for new, current year production equipment. Demonstrator, used or lessor model equipment will not be accepted. All references to brand name shall be interpreted as brand name or equivalent. All questions shall be directed to the Purchasing Department, 609 989 6710.

EXCEPTIONS

If bidding an equivalent manufacturer, provide the manufacturer's published literature and list all exceptions with descriptions of each exception.

A certificate of origin will be provided with the equipment upon delivery. Any questions regarding the bid must be directed to purchasing.

Upon delivery, vendors must provide set-up, operating training by an authorized manufacturer's representative and two sets of training manuals. All equipment shall include standard safety features.

As this is a cooperative bid, the awarded vendor(s) may provide the equipment herein bid upon to local governmental contracting units located within the County of Mercer without substitution or deviation from specifications, size, features, quality, price or availability as herein set forth. It is understood that orders will be placed directly by the contracting units, subject to the terms of the contract to be awarded by the County of Mercer, and that no additional service or delivery charges will be allowed. References to brand names shall be interpreted as brand or equivalent.

All equipment shall be delivered F.O.B destination with delivery charge included, within 90 days from receipt of purchase order. All equipment shall be delivered as stated above with to the **Mercer County Highway Division at 300 Scotch Road, West Trenton, NJ 08628.**

WARRANTY

The awarded vendor shall provide the warranty as stated in the specifications.

AWARDED CONTRACTOR SHALL PROVIDE OPERATING TRAINING BY AN AUTHORIZED MANUFACTURER'S REPRESENTATIVE UPON DELIVERY OF EQUIPMENT. VENDORS MUST SPECIFY THE MANUFACTURER'S CUT-OFF DATE.

VENDOR WILL HOLD PRICING FIRM FOR ONE YEAR

YES NO

BID SPECIFICATIONS
ONE (1) FORD F550 SERVICE BODY TIRE TRUCK WITH CRANE AND INVERTER
FOR USE BY MOTOR POOL

Model year 2019 or newer Ford F550 Chassis Cab Regular Cab

169" Wheel base, 84" CA
Color – white
6.7L V8 diesel engine
6 Speed automatic transmission
12-volt power points (2)
40-gallon fuel tank capacity
DEF tank
4 wheel drive
Manual locking hubs
19500 GVWR
Alternator – 220 AMP
Battery- 750CCA, 78AH Dual
225/75Rx19.5 BSW A/P Tire
Full size spare wheel and tire
Grab handle on passenger side A-pillar
Quad beam halogen headlamps
Power door locks
Power windows
Remote keyless entry system – to include 4 keys and fobs
Tilt/telescoping steering column
Vinyl floor covering
Windshield wipers – variable-intermittent
Running Boards
License plate bracket
Rear view backup camera
Tinted glass
Vinyl Seat 40/20/40

Comply: Yes_____ No_____

Exceptions:_____

Standard Safety & Security

- 3-point safety belts for all seating positions
- AdvanceTrac with RSC (roll stability control)
- Airbags – driver and front passenger

- Brakes – 4 wheel disc with anti-lock brake system (ABS)
- SOS Post-Crash Alert System
- Tire pressure monitoring system

Miscellaneous

- Delivery to Mercer County Motor Pool, 300 Scotch Rd, Bldg 4, West Trenton, NJ 08628
- Vehicle to be titled to the County of Mercer with registration and tags included, title will state "County of Mercer"
- Warranty – bumper to bumper: 3 years/36,000 miles

Comply: Yes_____ No_____

Exceptions:_____

J SERIES SERVICE BODY

General

- It is the intent of this bid to specify an 11' service sign body to be up fitted on a chassis with an 84" CA

Comply: Yes_____ No_____

Exceptions:_____

Dimensions

- 133-1/4" Overall length
- 94" Overall width
- 60" body height
- 54" floor width
- 44" floor height to top of compartments
- 18" floor height from top floor
- 20" compartment depth
- Streetside Compartmentation with master lock:
 - o First Vertical: 34-1/4" 4 adjustable shelves
 - o Second Vertical: 21" 4 adjustable shelves

- Horizontal: 52-1/4' x 38-1/2" high, overlapping doors, bolt in bins with shelf above
- Rear Vertical: 25-1/4" 4 adjustable shelves
- Curbside Compartmentation with master lock:
 - First Vertical: 34-1/4" C-Tech Aluminum tool cabinet push lock draws (2) 7" Drawers, (3) 5" Drawers, (4) 3" Drawers, with adjustable shelf above
 - Second Vertical: 21" 4 adjustable shelves
 - Horizontal: 52-3/4" x 38-1/2" high, overlapping doors, bolt in bins with shelf above
 - Rear Vertical: 25-1/4"x 40"H 1 adjustable shelf

Comply: Yes_____ No_____

Exceptions:_____

Body Shell

- Is to be constructed of 14 gauge two-sided A40 Galvanneal steel
- The compartment tops and backs are to be a one piece seamless design
- All door, door openings, drip rails, and other exposed steel edges are to be hemmed for strength, safety, and resistance to corrosion

Comply: Yes_____ No_____

Exceptions:_____

Floor

- The floor plate is to be constructed of a minimum of 1/8" gauge treadplate with a 1-3/8" return flange on each side.
- The side compartment back panel should overlap and interlock with the floor flange, providing support for the weight of the side compartment.

Comply: Yes_____ No_____

Exceptions:_____

Understructure

- Cross sills are to be constructed from 11 gauge steel with 50,000 psi minimum yield strength.
- Cross sills (4), End rails (1) and Longitudinal sills (2)

Comply: Yes_____ No_____

Exceptions:_____

Doors

- Are to be constructed of 20 gauge two-sided A40 Galvanneal Steel.
- Are to be double paneled with internal reinforcements for durability and long life.

Comply: Yes_____ No_____

Exceptions:_____

Hinges

- Corrosion resistant all stainless steel continuous hinges are to be installed to provide full length support for the doors and pry proof security with a built in weather shield. **No exceptions**
- They are to be spot welded to the door frames and must be supported with a six year warranty. **No exceptions**

Comply: Yes_____ No_____

Exceptions:_____

Rotary Latches

- Corrosion resistant rotary latches shall be secured to the door panels by four threaded studs attached to the back of the latches. Latches must have zinc die cast handles with a brushed chrome finish that provides ample hand clearance surrounded by an injection-molded glass and mineral infused UV resistant nylon housing.
- The latches must also have an internal injection molded glass and mineral infused UV resistant nylon cover for protection from the contents of the compartments.

- The rotary latches are to be slam-latchable. The latching cams are to be elongated to allow the latches to move vertically relative to the lock strikes to prevent torsional damage.
- Microcellular urethane foam gaskets are to be installed between the latch flange and the outer door skin to prevent moisture from entering the compartment behind the latch. Lock cylinders are to be flush mounted for additional security.

Comply: Yes_____ No_____

Exceptions:_____

Door Strikers

- Adjustable strikers are to be affixed to the door frames with screws.
(welded-on door strikers are not acceptable)

Comply: Yes_____ No_____

Exceptions:_____

Door Seals

- Automotive "bulb type" neoprene door seals are to be installed by the manufacturer of the body on all door frames. (after market not acceptable)

Comply: Yes_____ No_____

Exceptions:_____

Door Retainers

- Double springs over center door retainers are to be installed on all vertical doors.
- Door retainers need to hold doors in positive open or closed position (Other types of retainers, like cables or chains, are not acceptable on vertical doors.)
- Horizontal doors are to be secured in an open position parallel to the ground by heavy duty chain retainers.

- The chain retainers must be easily removable so that the door can be opened to a full 180 degrees to be able to access the compartment in tight areas.

Comply: Yes_____ No_____

Exceptions:_____

Shelving

- Shelves are to be constructed of 18 gauge bright spangled galvanized steel.
- All shelves are to have hemmed dividers on 4" centers.
- Shelves need to have a minimum capacity rating of 250 lbs. No exceptions

Comply: Yes_____ No_____

Exceptions:_____

Exterior Prime Paint

- The body is to be completely immersed in electrodeposition gray epoxy prime paint featuring a zinc phosphate pre-coat and seal for additional corrosion protection.
- Prime paint is to be oven cured to provide a hard durable finish.
- Color to be white

Comply: Yes_____ No_____

Exceptions:_____

Interior Paint

- Is to be a mid-gloss, mar-resistant, light gray finish

Comply: Yes_____ No_____

Exceptions:_____

Undercoating

- The body is to be completely undercoated by the body manufacturer using a water base acrylic

Comply: Yes_____ No_____

Exceptions:_____

Installation

- The manufacturer of the body is to supply a recommended installation process along with detailed installation instructions that conform to all applicable FMVS Safety standards. Rear body to chassis mounting brackets need to incorporate bumper support as well as provide FMVSS 301 protection. Furthermore, the manufacturer of the body is to supply an owner manual describing the proper care and maintenance of the body for Morris County.

Comply: Yes_____ No_____

Exceptions:_____

Warranty

The following items are to be covered by a (6) year limited warranty to the first owner of record. No exceptions:

- Continuous Door Hinges (Guaranteed not to fail to operate or come off product.) No exceptions
- Latches and Lock Cylinders (Unconditional guarantee against failure.) No exceptions
- Shelves (Guaranteed not to fail in bending under a maximum 250 lb. rated load.) No exception
- Body has a no rust-through guarantee for (6) years. No exceptions

Comply: Yes_____ No_____

Exceptions:_____

Lighting

- Lighting is to meet all FMVSS standards. The wiring harness is to be encased in a plastic loom and all wires are to be colored for ease of troubleshooting. The wire harness must have connectors that are

compatible with Dodge, Ford, and GM chassis without splicing. The stop/tail/turn and backup lights are to be surface mounted in the rear of the body. All marker, clearance, and R.I.D. lighting is to be LED type lighting. Having incandescent lights in any of these locations is not acceptable.

- All interior wiring must be retained by a mechanical fastening system. Other methods of securing the wiring, such as adhesive-backed holders, are unacceptable.
- Light guards are to be installed by the body manufacturer to provide guard protection for stop/tail/turn and backup light harness and adaptor.

Comply: Yes_____ No_____

Exceptions:_____

Miscellaneous

- Van Air Pro Series 35 Compressor:
 - Reciprocating type, 2 cylinders, 35 cfm @ up to 175 PSIG
 - Engine Gasoline Honda 11 hp
 - 30 gallon air storage tank
 - 2 year warranty
- 4 LED Strobes in Grill – 8891004
- 2 Whelen 400 Series Amber LED in rear
- 2 2" white yellow LED amber strobes mounted at wheel wells on side of the body – 8891105
- Rosco back up camera with 7" color monitor
- Dejana Spray lining on interior of body floor, walls, and top of compartments.
- 6 recessed tie downs will be located evenly spaced in the floor down the street and curbside.
- Chocks and chock holder cut outs will be supplied, in curbside wheel well.
- LED Cabinet lighting
- Class V receiver Hitch with 2 D-Rings, 2-5/16" ball, back up alarm and 7 round trailer plug
- 56" Whelen Justice Light Bar:
 - 4 Corner Amber LED clear lenses
 - 2 LED facing forward spaced evenly from the middle to the corner
 - Ally and Takedown lights
 - Arrow stick on rear of light bar
 - Mounted on Bulkhead
- LED Go-Lights:
 - 2 Mounted on top of compartments at Rear
 - 1 Mounted top of compartment Curbside front compartment

- Thieman TT15:
 - 56"x42"x5" 2 piece expanded metal liftgate
 - Tire Rack
 - Push Button
- Aims Power Pure Sign Inverter: Must have 200 Amp alternator
 - 5,000 Watt continuous power
 - 10,000 Watt surge power
 - 12vDC Input
 - Switchable: 60hz or 50hz
 - (2) GFCI Outlets built in, rated at 20A each
 - On / Off Switch
- Ventura CT310KX – Mounted curbside in cargo area at rear by liftgate
 - Hydraulic Extension to 6'3"
 - Manual Extension to 9'3"
 - 1900 lb maximum lifting capacity
 - Literature must be supplied with bid with maximum capacity chart

Comply: Yes_____ No_____

Exceptions:_____
